Index

Bold type is used for contributors to this volume. The suffix e indicates editorial comment; c, a conference report; r, a book review. Abbreviations: fr, fibre-reinforced; grc, glass-reinforced cement; lw, lightweight; pfa, pulverised fuel ash.

accelerated ageing
  alkali-sensitive fr concrete, 75–80
  glass fr cements, 41–4, 68–73
acoustic properties
  coconut fr slabs, 23–4, 26–7
aerated concrete, 54r
ageing (see also accelerated ageing)
  casting delay and flexural strength of sandwich beams, 276–7
  early, 118–21, 207c
  glass fr cements, 68–73
  lw Aglite concrete, 253, 254, 256–9
Aglite, 249–60
Ajayi, E. O., Lasisi and Osunade, 'Technical notes: The influence of water–cement ratio and mix proportions on the strength characteristics of laterite–cement mortars', 201–3
Akihama, S., Suenaga and Banno, 'The behaviour of carbon fibre reinforced composites in direct tension', 159–68
Akinmusuru, J. O., 'Lateritic soil – cement bricks for rural housing', 185–8
Al-Adeeb, A. M. and Matti, 'Leaching corrosion of asbestos cement pipes', 233–40
Ali, M. A., Singh and Majumdar, 'Properties of grc containing pfa', 65–74
alkali-sensitive fibres
  durability of concrete, 75–80
Al-Khalaf, M. and Yousif, 'Use of rice husk ash in concrete', 241–8
Alwis, W. A. M. and Mansur, 'Reinforced fibre concrete deep beams with web openings', 263–71
γ-aminopropyltriethoxysilane, 93–8
asbestos
  leaching corrosion of cement pipes, 233–40
  replacement materials, 63e, 123–4c
ASTM single block shear tests, 3, 4–7, 9–12
autoclaved aerated concrete, 54r
bamboo fr concrete, 141e
Banno, T., Akihama and Suenaga, 'The behaviour of carbon fibre reinforced cement composites in direct tension', 159–68
beams, steel fr
  deep reinforced, with web openings, 263–70
  flexural strength, 273–8
  torsional strength of prestressed, 81–91
Beaudoin, J. J. and Feldman, 'Durability of porous systems impregnated with dicyclopentadiene-modified sulphur', 13–18
bending fatigue
  epoxy-coated steel reinforced concrete, 104, 106–8, 115
Bergstrom, S. G. and Gram, 'Durability of alkali sensitive fibres in concrete', 75–80
bonding
  epoxy coated reinforcing steel to concrete, 102–3, 115
  interfacial, in steel fibre–cement matrix under flexure, 29–37
book reviews, 53–64r, 127–31r, 283r
British Standard single block shear tests, 3, 4–12

calcium carbonate microfiller, 93–8
carbon fr cement composites, 159–68
carbon fibres, 159
cement
  hydraulic, 283r
  portland, 13–17, 283r, 129–30
  problems in developing countries, 206c
  structure and performance, 129–30r
  ultra-rapid hardening (jet), 131r
cement composites
  carbon fr, in direct tension, 159–68
  Cem-FIL glass fr concrete, 75–80
  ferrocement crack widths, 169–70
  glass fr containing pfa, 65–74
  lateritic soil bricks, 185–8
  polymer-ferrocements, 151–7
  testing of fr, 217e
Chua, H. C., Dhir and Mays, 'Lightweight structural concrete with Aglite aggregate: mix design and properties', 249–61
coconut fr corrugated slabs, 19–27
Codes of Practice, 192–3, 196, 199, 217e
composite materials, 127–8r
compressive strength
  development in plain and steel fr concrete, 118–19
  epoxy-coated steel reinforced beams in marine environment, 108–9
  laterite–cement mortars, 201–3
  lateritic soil-cement bricks, 186–8
  lw Aglite concrete, 251–5, 256–9
  lw concrete, 144, 145
  phenol–formaldehyde resin concrete, 93–8
  reinforced deep beams with web openings, 267
  rice husk ash cements, 243, 245–7, 248
  steel fr concrete, 219–31, 275
  steel fr concrete at high temperatures, 180, 181–2, 183
  steel fr concrete at very low temperatures, 49–50
conferences and symposia forthcoming, 57–60c, 133–7c, 209–14c, 284–8c
  reports, 123–5c, 205–8c, 279–81c
Conplast 337, 250–2, 259
corrosion
  leaching in asbestos cement pipes, 233–40
  protection of reinforcing steel by epoxy coating, 99–115
  repair in reinforced concrete, 281c
  resistance of polymers, 63e
cost comparison
  lw and dense aggregate concrete, 56r
courses, educational, 61, 139, 215
cracking
  carbon fr cement composites in tension, 162, 166–8
  coconut fr slabs after flexure, 24, 25
  corrosion of asbestos cement pipes, 238
  corrosion of reinforcing steel, 110–13, 115
  crack widths of ferrocement composites in flexure, 155, 156, 169–77, 195–7, 200
  prestressed concrete beams, 85–91
  reinforced deep beams with web openings, 265–8
  steel fr concrete in compression,

cracking continued
223–6, 229–31
cryogenic concrete, 124–5c
curing
glass fr cements, 66, 67, 70
lw Aglite concrete, 253, 254
cyclic loading, see fatigue behaviour

Das Gupta, N. C., Paramasivam and Nathan, 'Coconut fibre reinforced corrugated slabs', 19–27
Demura, K., Neelamegam, Ohama, Suzuki and Shirai, 'Flexural behaviour of polymer-ferrocements with various polymer mortars as matrices', 151–7
density
lw Aglite concrete, 252, 253, 254
design
cryogenic concrete structures, 124–5c
new concrete materials, 130–1r
post-tensioned flat-slab floors, 131r
precast concrete, 54–5r
recommendations for lw concrete, 256–9
Desayi, P. and Ganesan, 'Determination of maximum crack width in ferrocement flexural elements of channel cross section', 169–77
developing countries
building material requirements, 141e, 185, 205–6c, 279c
Dhir, K., Mays and Chua, 'Lightweight structural concrete with Aglite aggregate: mix design and properties', 249–61
dicyclopentadiene-modified sulphur impregnated porous systems, 13–17
durability
alkali-sensitive fibres in concrete, 75–80
porous systems impregnated with modified sulphur, 13–17
testing methods, 280c

Ealing Broadway Centre bridge, 142
elastic properties (see also stress–strain characteristics)
glass fr cements containing pfa, 68, 70
steel fr concrete in compression, 220–2
steel reinforced concrete beams in marine environment, 109, 114, 115
elasticity, modulus of
carbon fr cement composites in tension, 162, 163, 165, 166
lw Aglite concrete, 255–6, 258, 259
steel fr concrete at high temperatures, 180, 181, 182
sulphur-impregnated porous systems, 14–17
embrittlement of alkali-sensitive fibres in concrete, 75–80
epoxy resins
corrosion protection of reinforcing steel, 99–115
fatigue behaviour, 1e
expanded polystyrene concrete, 130–1r

failure mode
corrosion of asbestos cement pipes, 234, 235–6, 238
lw concrete in flexure, 196–7, 199
reinforced deep beams with web openings, 265–8
steel reinforcement, 197, 199, 281c
fatigue behaviour, 1e
bending of epoxy coated steel reinforced concrete beams, 104, 106–8, 115
concrete structures, 53–4r
cyclic temperature tests, 48–50
polymers, 55–6r
tensile strength of lw concrete, 143–9
Feldman, R. F. and Beaudoin, 'Durability of porous systems impregnated with dicyclopentadiene-modified sulphur', 13–18
ferrocement
flexural behaviour with polymer mortar matrices, 153–7
maximum crack width determination in flexural elements, 169–77
fibre distribution
effect on strength, 34–7, 275–6, 277
fibre failure patterns, 43
fibre pull-out
concrete strength tests, 207c
glass fr cements containing pfa, 67, 73
steel fr cement, 29–37
fibre volume effects
carbon fr cement composites in direction tension, 162–8
flexural strength of beams, 275–6, 277
fracture behaviour of steel fr concrete, 224–6, 227, 228–9
ultimate strength of deep reinforced beams, 268
fire performance, 179–83, 205c
firing temperature of lateritic soil–cement bricks, 186–7
flexural strength
coconut fr slabs, 23, 24–5
effect of embrittlement, 76
glass fr cements containing pfa, 70, 72
polymer-ferrocements, 151–7
pull-out tests and interfacial bonding of steel fibre–cement matrix, 30–7
steel fr concrete beams, 273–8
steel reinforced concrete beams, 104–6, 114, 115, 190–200
flexural tensile strength
steel fr concrete at high temperatures, 180, 181, 182–3
fly ash, see pulverised fuel ash
foundations, 53r
fracture
mechanics, 55r
steel fr concrete in compression, 219–31
fracture surface
Cem-FIL/Pozament glass fr cement, 73
phenol–formaldehyde resin mortars, 96–8

Ganesan, N. and Desayi, 'Determination of maximum crack width in ferrocement flexural elements of channel cross section', 169–77
glass, vycor, 13–17
glass fr cement, 283r
containing pfa, 65–74
SIC test, 39–45
glass fr concrete, 75–80
Gram, H.-E., and Bergstrom, 'Durability of alkali sensitive fibres in concrete', 75–80
grid reinforcement polymers, 63e, 123c

high temperature performance of concrete, 179–83, 205c
housing, low cost, 185, 205–6c
Hussain, A. A. and Raouf, 'Technical notes: Some properties of steel fibre concrete at early ages', 117–21

impact strength
epoxy coatings on steel, 102
glass fr cements, 69–72
interfacial interactions
steel fibre–cement matrix bond in flexure, 29–37
sulphur-impregnated porous systems, 16–17

joints for seals and bearings, 53r

Kareem-Palanjian, A. and Narayanan, 'Torsion in prestressed concrete beams containing steel fibres', 81–91
Khandelwal, B. L., Sood and Krishnamoorthy, 'The effect of silane coupling and microfiller on the strength of phenol–formaldehyde resin concrete', 93–8

Kobayashi, K. and Takewaka, 'Experimental studies on epoxy coated reinforcing steel for corrosion protection', 99–116
Krishnamoorthy, S., Sood and Khandelwal, 'The effect of silane coupling agent and microfiller on the strength of phenol–formaldehyde resin concrete', 93–8

Lambert, G. H. and Swamy, 'Flexural behaviour of reinforced concrete beams made with fly ash coarse aggregates', 189–200
Lasisi, F., Ajayi and Osunade, 'Technical notes: The influence of water–cement ratio and mix proportions on the strength characteristics of laterite–cement mortars', 201–3
laterites
  compressive strength of mortars with cement, 201–3
  in soil–cement bricks, 185–8
leaching corrosion in asbestos cement pipes, 233–40
lightweight aggregate concrete
  Aglite in structural concrete, 249–60
  cost comparison, 56r
  Ealing Broadway Centre Bridge, 142
  fatigue behaviour, 1e
  made from pfa, 189–200
  tensile fatigue strength, 143–9
lightweight concrete, 54r, 130–1r
lime, free, 233–4, 236–40
liquefied gas storage, 47–8, 124–5c
Litherland, K. L., Maguire and Proctor, 'A test method for the strength of glass fibres in cement', 39–45
low cost building materials, 185–8, 205–6c, 279c
low temperatures
  cryogenic concrete, 124–5c
  fatigue behaviour, 1e
  strength and deformation of steel fr concrete, 47–51

Maguire, P., Litherland and Proctor, 'A test method for the strength of glass fibres in cement', 39–45
Majumdar, A. J., Singh and Ali, 'Properties of grc containing pfa', 65–74
Mangat, P. S. and Motamedi-Azari, 'Influence of steel fibre reinforcement on the fracture behaviour of concrete in compression', 219–32
Mangat, P. S., Motamedi-Azari and Shakor Ramat, 'Steel fibre-cement matric interfacial bond characteristics under flexure', 29–37
Mansur, M. A. and Alwis, 'Reinforced fibre concrete deep beams with web openings', 263–71
marine environment
  corrosion protection in, 99, 108–115
  cryogenic concrete, 124c
  fatigue behaviour, 1e
Matti, M. A. and Al-Adeeb, 'Leaching corrosion of asbestos cement pipes', 233–40
Mays, C., Dhir and Chua, 'Lightweight structural concrete with Aglite aggregate: mix design and properties', 249–61
mix proportions
  effect on compressive strength of laterite–cement ratios, 201–3
  lw Aglite concrete, 251–2, 253
models
  computerised shear tests, 6–12
  deep beams with web openings, 263–4, 267, 269–70
  lattice, for steel fr concrete, 224, 225
mortar
  compressive strength of lateritic, 201–3
  polymer, 29–37, 151–7
Motamedi-Azari, M. and Mangat, 'Influence of steel fibre reinforcement on the fracture behaviour of concrete in compression', 219–32
Motamedi-Azari, M., Mangat and Shakor Ramat, 'Steel fibre–cement matrix interfacial bond characteristics under flexure', 29–37

Narayanan, R. and Kareem-Palanjian, 'Torsion in prestressed concrete beams containing steel fibres', 81–91
Nathan, G. K., Paramasivam and Das Gupta, 'Coconut fibre reinforced corrugated slabs', 19–27
natural fibre reinforcement, 75–80, 141e, 206c
Neelamegam, M., Ohama, Demura, Suzuki and Shirai, 'Flexural behaviour of polymer-ferrocements with various polymer mortars as matrices', 151–7
non-destructive tests, 106–8, 217e, 280–1c
Novolac, 93–8

O'Connor, D. J., 'An evaluation of test methods for shear modulus of sandwich cores', 3–12
Ohama, Y., Neelamegam, Demura, Suzuki and Shirai, 'Flexural behaviour of polymer-ferrocements with various polymer mortars as matrices', 151–7
Osunade, J. A., Lasisi and Ajayi, 'Technical notes: The influence of water–cement ratio and mix proportions on the strength characteristics of laterite–cement mortars', 201–3

Paramasivam, P., Nathan and Das Gupta, 'Coconut fibre reinforced corrugated slabs', 19–27
phenol–formaldehyde resin concrete, 93–8
polymer composites
  as asbestos replacements, 63e, 123–4c
  expanded polystyrene concrete, 130–1r
  fatigue behaviour, 1e
  grid reinforcements, 123c
  styrene–butadiene modified pfa in glass fr cement, 68–70, 72, 74
polymer concrete, 280c
  compressive strength of phenol–formaldehyde resin composite, 93–8
polymer mortars
  bonding of steel fibres, 29–37
  flexural behaviour of ferrocements, 151–7
polymers, 55–56r
polypropylene fr cement, 56r
polystyrene concrete, expanded, 130–1r
portland cement, 283r
  durability of sulphur-impregnated paste, 13–17
  structure and performance, 129–30r
post-tensioned flat slabs, 131r
pozzolans
  pfa, 65–74, 190–200, 250–3, 259, 279–80c
  Pozament, 65, 66, 68
  rice husk ash, 241–8
precast concrete, 54–5r
prestressed concrete
  torsional strength of steel fr, 81–91
prestressed steel reinforcement in cryogenic concrete, 124c
probe penetration tests, 207c
Proctor, B. A., Litherland and Maguire, 'A test method for the strength of glass fibres in cement', 39–45
pull-out, see fibre pull-out
pulse velocity tests, see ultrasonic pulse velocity tests
pulverised fuel ash (fly ash, pfa), 189–90, 279–80c
  flexural strength of reinforced concrete, 190–200
  in glass fr cement, 65–74
  in lw Aglite concrete, 250–3, 259
Purkiss, J. A., 'Steel fibre reinforced concrete at elevated temperatures', 179–84

Raouf, Z. A. and Hussain, 'Technical notes: Some properties of steel fibre concrete at early ages', 117–21
Ravindrarajah, R. S. and Tam, 'Flexural strength of steel fibre reinforced concrete beams', 273–8
reinforced concrete
deep beams with web openings, 263–70
epoxy coated steel for corrosion protection, 99–115
flexural behaviour of lw, 191–200
repair of corroded, 281c
reinforcement
corrosion protection of steel, 99–115
cryogenic concrete structures, 124c
grid, 63e, 123c
repair of corroded reinforced concrete, 281c
rheology of fresh concrete, 128–9r
rice husk ash, 241–8, 279c
Rostasy, F. S. and Sprenger, 'Strength and deformation of steel fibre reinforced concrete at very low temperature', 47–51

Saito, M., 'Tensile fatigue strength of lightweight concrete', 143–9
sandwich structures
shear modulus of cores, 3–12
steel fr concrete beams, 273–8
sea water, see marine environment
serviceability limit states, 197–9
Shakor Ramat, B. B., Mangat and Motamedi-Azari, 'Steel fibre–cement matrix interfacial bond characteristics under flexure', 29–37
shale, expanded
tensile fatigue strength of lw concrete containing, 143–9
shear modulus
sandwich cores, 3–12
shear strength
reinforced deep beams with web openings, 268
steel fr concrete at early ages, 120–1
Shirai, A., Neelamegam, Ohama, Demura and Suzuki, 'Flexural behaviour of polymer-ferrocements with various polymer mortars. as matrices', 151–7
shrinkage
drying, of lw Aglite concrete, 256, 258–9, 260
rice husk ash pastes and mortars, 243, 247
silane coupling agent, 93–8
silica fume additive, 77, 79
Singh, B., Majumdar and Ali, 'Properties of grc containing pfa', 65–74
sisal fr concrete, 75–80
slabs, post-tensioned, 131r
Sood, R. K., Krishnamoorthy and Khandelwal, 'The effect of silane coupling agent and microfiller on the strength of phenol–formaldehyde resin concrete', 93–8
sound absorption, 23–4, 26–7
Sprenger, K. H. and Rostasy, 'Strength and deformation of steel fibre reinforced concrete at very low temperature', 47–51
steel fr cement
interfacial bond characteristics in flexure, 29–37
steel fr concrete
at early ages, 117–21
at high temperatures, 179–83
at very low temperatures, 47–51
fatigue behaviour, 1e
flexural strength of beams, 273–8
fracture behaviour in compression, 219–31
reinforced deep beams with web openings, 263–70
torsional strength of prestressed beams, 81–91
steel reinforcement
corrosion protection by epoxy coating, 99–115
Strand in Cement (SIC) test, 39–45
strength (see also compressive strength, flexural strength, flexural tensile strength, impact strength, shear strength, tensile strength, torsional strength) tests, 217e
stress distribution in ferrocement flexural members, 170
stress–strain characteristics
carbon fr cement composites in tension, 161–2, 164–5, 168
coconut fibre, 20, 21
fr cement embrittlement and durability, 76
glass fr cements containing pfa, 70, 73
lw Aglite concrete, 255–6, 257, 258
lw concrete under repeated tensile loading, 147–9
steel fr concrete at very low temperatures, 49, 50, 51
steel fr concrete in compression, 220–3, 224, 226–8, 229
steel reinforcement lw concrete in flexure, 193–5
styrene–butadiene modified pfa, 68–70, 72, 74
Suenaga, T., Akihama and Banno, 'The behaviour of carbon fibre reinforced composites in direct tension', 159–68
sulphur-containing concrete, 130r, 279c
sulphur impregnated porous systems, 13–17
Suzuki, S., Neelamegam, Ohama, Demura and Shirai, 'Flexural behaviour of polymer-ferrocements with various polymer mortars as matrices', 151–7
Swamy, R. N., 1e, 63e, 141e, 217e
Swamy, R. N. and Lambert, 'Flexural behaviour of reinforced concrete beams made with fly ash coarse aggregates', 189–200
swelling
rice husk ash pastes and mortars, 243, 247

Takewaka, K. and Kobayashi, 'Experimental studies on epoxy coated reinforcing steel for corrosion protection', 99–116
Tam, C. T. and Ravindrarajah, 'Flexural strength of steel fibre reinforced concrete beams', 273–8
temperature
dependence of SIC measurements, 44
high, 179–83, 205c
low, 1e, 47–51, 124–5c
tensile strength
alkali-sensitive fr concrete, 77, 78
carbon fr cement composites, 159–68
fatigue tests on lw concrete, 143–9
glass fr cements containing pfa, 69
lw Aglite concrete, 255, 256, 258, 259
reinforced deep beams with web openings, 267
SIC test for glass fibres in cement, 39–45
steel fr concrete at very low temperatures, 50
steel fr concrete beams, 275
test methods
durability of concrete, 280c
non-destructive, 206–8c, 217e, 280–1c
shear modulus of sandwich cores, 3–12
strength of glass fibres in cement (SIC), 39–45
strength of concrete, 206–8c, 217e
tensile fatigue strength of lw concrete, 143–5
two-point workability, 128–9r
ultrasonic pulse velocity, 117–21, 180–3
thermal conductivity
coconut fr slabs, 23, 26
thermal deformation

thermal deformation continued
steel fr concrete at very low temperatures, 48–50
torsional ductility
prestressed concrete beams, 85–91
torsional strength
steel fr prestressed concrete beams, 81–91
toughness
polymer-ferrocements, 154–5, 157
steel fr concrete in compression, 228–9

ultrasonic pulse velocity tests
steel fr concrete, 117–21, 180–3
underground works, 56r

volume changes, see shrinkage, swelling
vycor glass, 13–17

waste materials
concrete composites, 131r, 189–90, 279c
rice husk ash, 241–8, 279c
water–cement ratio
effect on compressive strength, 201–3, 251, 252, 254
water content
effect on autoclaved aerated concrete, 54r
effect on compressive strength of rice husk ash mortar, 246–7
water hardness and corrosion, 233–4, 236–9
weathering
glass fr cements containing pfa, 66, 68–74
workability
lw Aglite concrete, 251, 252
two-point test, 128–9r

Yousif, H. and Al-Khalaf, 'Use of rice husk ash in concrete, 241–8